

dm1


high frequency vibration exciter

Application

dm1 is specially designed for the demands of high frequency vibration calibration and testing. Due to its unique electrodynamic drive technology dm1 achieves high force and thus acceleration rating. A special designed flexure bearing system combines the performance needed for high class calibration and the robustness for testing without the need of compressed air. The technical ceramic used to make the armature of the shaker is responsible for the broad frequency range up to 50 kHz and the robustness against wear.

Features

- Ceramic armature with replaceable steel insert for DUT mounting
- Flexure bearing
 - Fulfills ISO 16063-11 requirements
 - High cross force capability
 - No DUT weight compensation needed
 - No need for compressed air
- Built in standard accelerometer



Technical Data

- Frequency range: 5 Hz – 50 kHz, First axial resonance > 50 kHz
- Force rating: max. 70 N / 100 N (continuous / interval)
- Maximum acceleration: 280 m/s² pk / 400 m/s² pk (continuous / interval)
- Maximum usable stroke: 8 mm (pk-pk)
- Cross motion: according to ISO 16063 -11 / 21 (5 - 10 % up to 50 kHz)
- Internal reference standard (IEPE, 1 mV/m/s²), Smooth response > 50 kHz
- Max. payload: 350 gram, max. side load: 30 N
- Magnetic stray field: 5 mT at DUT position



dm1

high frequency vibration exciter

Dimensions and Weight

- Height: 120 mm
- Weight: 12 kg

Remarks

- Technical data achieved with 500 W Power Amplifier (BEAK BAA500)
- All data refer to room temperature

